

 **PALIO**
by Karndean

3 LUXURY FLOORING RANGES

**DESIGNED
FOR THE TRADE
TO FIT**



Palio
Clic

Palio
Core

Palio
LooseLay



QUICK AND EASY
TO INSTALL



DURABLE



LOW
MAINTENANCE



WATERPROOF



COMPATIBLE WITH
UNDERFLOOR
HEATING



CONTENTS

WHAT IS PALIO BY KARNDDEAN?	4
RANGE OVERVIEW	5
OUR PRODUCTS	
PALIO CLIC PALIO CORE	6
PALIO LOOSELAY	16
TECHNICAL INFORMATION	
PALIO CLIC PALIO CORE	15
PALIO LOOSELAY	25
INSTALLATION GUIDELINES	
PALIO CLIC PALIO CORE	14
PALIO LOOSELAY	24
SUPPORT AND WHERE TO BUY	26

WHAT IS PALIO BY KARNDEAN?

Palio by Karndean is luxury vinyl flooring available in three product ranges, Palio Clic, Palio Core and Palio LooseLay, offering quick and easy installation without the need for a specialist fitter.



QUICK AND EASY TO INSTALL

Using LooseLay and our patented click-locking mechanisms.



WATERPROOF

Won't swell, crack or warp when wet.



HIGHLY REALISTIC DESIGNS

Designed by Karndean's in-house product team to perfectly replicate real wood and stone.



SOFT, WARM AND QUIET UNDERFOOT

No cold tiles, no clicking shoes.



DURABLE

Won't warp or crack like real wood and stone. Lifetime guarantee.



HYGIENIC

Unlike carpets, our floors don't hold dust, dirt, pollen or other allergens.



LOW MAINTENANCE

Clean easily with a sweep and mop. No sanding, varnishing or staining.



UNDERFLOOR HEATING

Compatible with underfloor heating up to 27°C.

What makes our floors different?

Palio by Karndean is luxury vinyl flooring. It's not like typical vinyl. It doesn't come in rolls or sheets, and it doesn't need to be glued down.

Instead, it comes in robust, pre-cut planks and tiles. Our highly realistic designs look just like the wood and stone materials they're inspired by.

But unlike a wood or stone floor Palio flooring is easy to install. All you need to do is simply click or lay it in place.



CP4504 | RCP6504 MONTIERI

RANGE OVERVIEW



The Palio Clic range is quick and easy to install with a patented and familiar click-locking mechanism, and doesn't require adhesive.



PATENTED CLICK-LOCKING SYSTEM



NO NEED FOR ADHESIVE



Available in the same realistic wood and stone look designs as Palio Clic, Palio Core offers a rigid core LVT construction which provides more robustness on uneven subfloors and is our most acoustically friendly Palio product.



PATENTED CLICK-LOCKING SYSTEM




NO NEED FOR ADHESIVE



LAYS OVER MOST EXISTING HARD FLOORS



REDUCES IMPACT NOISE TRANSFER BY 19dB



Realistic wood and stone look designs, available in a loose lay format with a friction grip backing. If a plank or tile gets damaged, you can easily replace it without taking the whole floor up.



FRICITION GRIP BACKING



REDUCES IMPACT NOISE TRANSFER BY 13dB



CAN BE LAID IN ROOMS WITH 95% RELATIVE HUMIDITY



EASY TO REPLACE



NO EXPANSION GAP





PALIO CLIC

Palio Clic comes in a range of highly realistic wood and stone designs. It uses our patented click-locking system, so you can simply click the pre-cut planks and tiles into place. You won't even need adhesive.

PALIO CORE

Palio Core comes in the same range of designs as Palio Clic, but it combines our simple click-locking system with a rigid core construction which provides more robustness on uneven floors. And with its acoustic foam backing, it can reduce noise transfer by 19dB.

Palio Clic and Palio Core comparison

Feature	Palio Clic	Palio Core
 Patented click-locking system	✓	✓
 No need for adhesive	✓	✓
 Lays over most existing hard floors		✓
 Reduces impact noise transfer by 19dB		✓



WOOD AT A GLANCE

1220mm x 179mm (48" x 7")



SORANO

Palio Clic **CP4508**

Palio Core **RCP6508**



CRESPINA

Palio Clic **CP4505**

Palio Core **RCP6505**



AREZZO

Palio Clic **CP4503**

Palio Core **RCP6503**



VETRALLA

Palio Clic **CP4506**

Palio Core **RCP6506**



MONTIERI

Palio Clic **CP4504**

Palio Core **RCP6504**



ASCIANO

Palio Clic **CP4502**

Palio Core **RCP6502**



BOLSENA

Palio Clic **CP4507**

Palio Core **RCP6507**



LUCCA

Palio Clic **CP4509**

Palio Core **RCP6509**

STONE AT A GLANCE

307mm x 600mm (12" x 23.6")



MURLO

Palio Clic **CT4302**

Palio Core **RCT6302**



VOLTERRA

Palio Clic **CT4301**

Palio Core **RCT6301**



PIENZA

Palio Clic **CT4303**

Palio Core **RCT6303**



CETONA

Palio Clic **CT4304**

Palio Core **RCT6304**



CT4302 | RCT6302 MURLO





SORANO
Palio Clic **CP4508** | Palio Core **RCP6508**
1220mm x 179mm (48" x 7")



AREZZO
Palio Clic **CP4503** | Palio Core **RCP6503**
1220mm x 179mm (48" x 7")



MONTIERI
Palio Clic **CP4504** | Palio Core **RCP6504**
1220mm x 179mm (48" x 7")



BOLSEÑA
Palio Clic **CP4507** | Palio Core **RCP6507**
1220mm x 179mm (48" x 7")



CP4504 | RCP6504 MONTIERI



CP4507 | RCP6507 BOLSEÑA





CRESPINA
Palio Clic **CP4505** | Palio Core **RCP6505**
1220mm x 179mm (48" x 7")



VETRALLA
Palio Clic **CP4506** | Palio Core **RCP6506**
1220mm x 179mm (48" x 7")



ASCIANO
Palio Clic **CP4502** | Palio Core **RCP6502**
1220mm x 179mm (48" x 7")



LUCCA
Palio Clic **CP4509** | Palio Core **RCP6509**
1220mm x 179mm (48" x 7")



CP4505 | RCP6505 CRESPINA



CP4509 | RCP6509 LUCCA





MURLO
Palio Clic **CT4302** | Palio Core **RCT6302**
307mm x 600mm (12" x 23.6")



PIENZA
Palio Clic **CT4303** | Palio Core **RCT6303**
307mm x 600mm (12" x 23.6")



VOLTERRA
Palio Clic **CT4301** | Palio Core **RCT6301**
307mm x 600mm (12" x 23.6")



CETONA
Palio Clic **CT4304** | Palio Core **RCT6304**
307mm x 600mm (12" x 23.6")



CT4302 | RCT6302 MURLO



CT4304 | RCT6304 CETONA

PALIO CLIC | PALIO CORE Installation guidelines

Please refer to palioflooring.com for the full installation instructions.



1. Using a knife and a straight edge measure the first plank to no smaller than the width of the plank.



2. Score the plank once and snap it so you have the desired length.



3. No need for adhesive, click and lock the planks into place.



4. Continue to fit the rest of the floor. Remember to leave a 5mm expansion gap.

PALIO CLIC | PALIO CORE Technical specification

Palio
Clic

PALIO CLIC

Palio
Core

PALIO CORE

	STANDARD	PALIO CLIC RESULT	PALIO CORE RESULT	
	SIZE	EN ISO 24342	Plank: 1220 mm x 179 mm (48.7" x 7") Tile: 307 mm x 600 mm (12" x 23.6")	Plank: 1220 mm x 179 mm (48" x 7") Tile: 307 mm x 600 mm (12" x 23.6")
	LOCKING SYSTEM*		2G	2G
	THICKNESS	EN ISO 24346	4.5 mm	6.5 mm
	WEAR LAYER	EN ISO 24340	0.4 mm	0.55 mm
	SURFACE TREATMENT		PU coating	PU coating
	GUARANTEE	Commercial Domestic	12 years** Lifetime guarantee**	15 years** Lifetime guarantee**
	MASS	EN ISO 23997	9050 g/m ²	7480 g/m ²
	STANDARDS	EN 649 / EN ISO 10582 EN 16511	Pass	Pass:-Multilayer modular floorcovering panels
	CLASSIFICATION	EN 685 / EN ISO 10874- Commercial EN ISO 10874 Commercial EN 685 / EN ISO 10874- Domestic	32: Commercial general 23: Domestic heavy	33: Commercial heavy 23: Domestic heavy
	REACTION TO FIRE	EN 13501-1	Bfl-s1	Bfl-s1
	STAINING RESISTANCE	EN ISO 26987/EN 423 EN 438-2	Excellent	Pass (grade 5)
	LIGHT FASTNESS	EN ISO 105-B02	≥7	Pass ≥6
	ABRASION RESISTANCE	EN 649 EN ISO 10582 EN 13329 Annex E	Group T Type 1	Pass 4000 cycles
	DIMENSIONAL STABILITY	EN 434 / EN ISO 23999 BS EN ISO 23999	Pass	Pass ≤ 0.25%
	SWELLING	ISO 24336		Pass (0.2%)
	ACOUSTIC IMPACT NOISE REDUCTION	EN ISO 717-2 / EN ISO 140-8 EN ISO 10140-1:2016 / EN ISO 10140-3:2010+A1:2015	ΔL _w = 4 dB	ΔL _w = 19 dB ΔL _{lin} = 11 dB
	INDENTATION - RESIDUAL	EN 433 / EN ISO 24343-1 ISO 24343-1	Pass ≤0.1 mm	Pass ≤0.1 mm
	IMPACT RESISTANCE	EN13329 Annex F		Pass ≥1800 mm
	CASTOR CHAIR CONTINUOUS USE	EN 425/ ISO 4918 ISO 4918/ EN 425	Pass	Pass 25,000 cycles
	THERMAL RESISTANCE	ISO 8302	0.0197 m ² K/W Suitable for underfloor heating. Max 27°C	0.052 m ² K/W Suitable for underfloor heating. Max 27°C
	SLIP RESISTANCE***	BS 7976 DIN 51130 DIN 51097 EN 13893	Plank: 63 (dry), 38 (wet) Tile: 52 (dry), 30 (wet) R10 Plank: B Tile: C DS	Plank: 63 (dry), 36 (wet) R10 DS
	LIGHT REFLECTANCE VALUE (LRV)	BS 8493:2008+A1:2010	See separate table	See separate table
	VOC EMISSION	ISO 16000	Indoor Air Comfort Gold	Indoor Air Comfort Gold
	ADHESIVE		None required; please install according to our installation instructions.	None required; please install according to our installation instructions.
	RECYCLING		Suitable	Suitable
	PHTHALATE FREE			Yes


CLIC PRODUCT	CORE PRODUCT	LRV
CP4502	RCP6502	11
CP4503	RCP6503	28
CP4504	RCP6504	26
CP4505	RCP6505	23
CP4506	RCP6506	10
CP4507	RCP6507	17
CP4508	RCP6508	41
CP4509	RCP6509	12
CT4301	RCT6301	27
CT4302	RCT6302	51
CT4303	RCT6303	40
CT4304	RCT6304	11

* Produced under Licence from Valinge Innovations

** Subject to terms. Please see our website.


***Slip resistance is measured on ex-factory product. Slip resistance in use will be affected by surface contamination, use and by how the product is maintained.

Manufactured to ISO 9001



PALIO LOOSELAY

Palio LooseLay comes in 14 different wood and stone designs. With its friction grip backing, it's easy to fit. It creates a strong bond with the subfloor using a calculated combination of weight and friction. And it's easy to repair. If a plank or tile gets damaged, you can quickly replace it without taking the whole floor up.



WOOD AT A GLANCE

1050mm x 250mm (41.3" x 9.85")



PALMARIA

LLP149



LAMPIONE

LLP147



TAVOLARA

LLP144



BUDELLI

LLP146



SICILIA

LLP142



LINOSA

LLP148



TORCELLO

LLP145



LEVANZO

LLP150



SARDINIA

LLP143




VIVARA

LLP151

STONE AT A GLANCE

500mm x 610mm (19.7" x 24")



TINO

LLT208




CAPRI

LLT209



NISIDA

LLT210



VULCANO

LLT211



LLP147 LAMPIONE





TAVOLARA
LLP144
1050mm x 250mm (41.3" x 9.85")



BUDELLI
LLP146
1050mm x 250mm (41.3" x 9.85")



TORCELLO
LLP145
1050mm x 250mm (41.3" x 9.85")



SICILIA
LLP142
1050mm x 250mm (41.3" x 9.85")



SARDINIA
LLP143
1050mm x 250mm (41.3" x 9.85")







PALMARIA
LLP149
1050mm x 250mm (41.3" x 9.85")



LAMPIONE
LLP147
1050mm x 250mm (41.3" x 9.85")



LEVANZO
LLP150
1050mm x 250mm (41.3" x 9.85")



LINOSA
LLP148
1050mm x 250mm (41.3" x 9.85")



VIVARA
LLP151
1050mm x 250mm (41.3" x 9.85")



LLP150 LEVANZO






TINO
LLT208
500mm x 610mm (19.7" x 24")



CAPRI
LLT209
500mm x 610mm (19.7" x 24")



NISIDA
LLT210
500mm x 610mm (19.7" x 24")



VULCANO
LLT211
500mm x 610mm (19.7" x 24")



LLT210 NISIDA



LLT210 NISIDA

PALIO LOOSELAY Installation guidelines

Please refer to palioflooring.com for the full installation instructions.



1. Using a knife and a straight edge measure the first plank to no smaller than the width of the plank.



2. Score the plank once and snap it so you have the desired length. You may need to use a knife to fully separate the plank.



3. Using a knife, chamfer the edge to get a symmetrical sloping edge so the plank fits tightly against the wall or another plank.



4. Lay the planks loose, the friction grip backing will hold the product to the floor. A tackifier around the edge of the room is recommended.

PALIO LOOSELAY Technical specification

Palio
LooseLay

PALIO LOOSELAY


	STANDARD	RESULT
	EN ISO 24342	Plank: 1050 x 250 mm (41.3"x9.85") Tile: 500 x 610 mm (19.7" x 24")
	EN ISO 24346	4.5 mm
	EN ISO 24340	0.55 mm
		PU coating
	Light industrial Commercial Domestic	15 years* 15 years* Lifetime guarantee*
		No
	EN ISO 23997	7550 g/m ²
	EN 649/EN ISO 10582	Pass
	EN 685/EN ISO 10874- Light industrial EN 685/EN ISO 10874- Commercial EN 685/EN ISO 10874- Domestic	42: Light industrial general 33: Commercial heavy 23: Domestic heavy
	EN 13501-1	B _{fl} -s1
	EN ISO 26987/EN 423	Excellent
	EN ISO 105-B02	7
	EN 649 EN ISO 10582	Group T Type 1
	EN ISO 24344	Pass
	EN 434/EN ISO 23999	≤ 0.10%
	EN ISO 717-2 / EN ISO 140-8	ΔL _W = 13 dB
	EN 433/EN ISO 24343-1	Pass ≤ 0.1mm
	EN 425/ISO 4918	Pass
	ISO 8302	0.0245 m ² K/W Suitable for underfloor heating. Max 27°C
	BS 7976 DIN 51130 DIN 51097 EN 13893	Plank: Dry: 61 Wet: 33 Tile: Dry: 66 Wet: 29 R10 Plank: B Tile: A DS
	BS 8493:2008+A1:2010	See separate table
	ISO 16000	Indoor Air Comfort Gold
	None required; please install according to our installation instructions.	
		Suitable

PRODUCT	LRV
LLPI42	26
LLPI43	20
LLPI44	34
LLPI45	27
LLPI46	27
LLPI47	38
LLPI48	21
LLPI49	46
LLPI50	25
LLPI51	9
LLT208	66
LLT209	44
LLT210	23
LLT211	10

*Subject to terms. Please see our website.

**Slip resistance is measured on ex-factory product. Slip resistance in use will be affected by surface contamination, use and how the product is maintained.

Manufactured to ISO 9001




FIND US ONLINE

palioflooring.com

The website offers a wealth of inspiration, including our installation videos which take you through a step by step guide to fitting all three of the Palio ranges with Roger Bisby from Skill Builder.

You can also view these on the Palio by Karndean YouTube channel.



Palio Clic installation guide
The Palio Clic range is quick and easy to install with a patented and familiar click-locking mechanism that doesn't require adhesive – see how to install here.

Palio Core installation guide
Palio Core offers a rigid core LVT construction which provides more robustness on uneven subfloors and is our most acoustically friendly Palio product – see how to install here.

Palio LooseLay installation guide
Realistic wood and stone look designs, available in a loose lay format with a friction grip backing – see how to install here.

[View all support](#)

FIND A STOCKIST

Simply log onto palioflooring.com where you can select a local stockist that has our Palio ranges in stock for you to pick up a sample or buy the product.

You can also contact our Trade team for more details about Palio by Karndean on **01386 820110** or for any technical questions you may have, contact our technical experts on **01386 820102**.



We provide a sample service so you can see and handle the planks and tiles that you are interested in.

To use our fast and convenient sample service call **01386 820110** or visit palioflooring.com to order a chip size sample.





CONTACT US...

Crab Apple Way
Evesham
Worcestershire
WR11 1GP
01386 820110
info@palioflooring.com

palioflooring.com

